

# — Supplementary Material —

## Unsupervised Human Action Recognition with Skeletal Graph Laplacian and Self-Supervised Viewpoints Invariance

Giancarlo Paoletti<sup>1</sup>  
giancarlo.paoletti@iit.it

Jacopo Cavazza<sup>1</sup>  
jacopo.cavazza@iit.it

Cigdem Beyan<sup>1,2</sup>  
cigdem.beyan@unitn.it

Alessio Del Bue<sup>1</sup>  
alessio.delbue@iit.it

<sup>1</sup> Pattern Analysis and Computer Vision (PAVIS)  
Istituto Italiano di Tecnologia (IIT)  
Genova, Italy

<sup>2</sup> Department of Information Engineering and Computer Science  
University of Trento  
Trento, Italy

---

This supplementary material includes the implementation details of our method (Section 1), ablation study performed to investigate how the initialization of Graph Laplacian weight matrix  $\mathbf{W}$  affect the performance of proposed AE-L (Section 2), confusion matrices obtained when our AE-L is applied on the testing data of NTU-60 [16] dataset (Section 3) and the comparisons between our AE-L and the state-of-the-art supervised and unsupervised skeleton-based human action recognition methods (Section 4). It is important to note that the results given in Section 4 are equivalent to the results shown in the *main paper* Section 4.1, and the table therein provides the quantitative values as summarised in the figure. We also demonstrate qualitative results comparing the reconstructed skeletons in Section 5.

## 1 Implementation Details

### 1.1 Data Pre-processing

We discard the missing time-frames as applied in Predict & Cluster [20]. We normalize each skeleton in terms of bone-length (in the range of [-1, 1]), followed by a regularization of the temporal length of each sample by setting it up to 100 time-frames (cutting frames of longer samples or replicating frames for shorter samples), and finally splitting data *w.r.t.* cross-subject, cross-view and cross-setup settings of benchmarks [11, 16]. This procedure is adapted from Predict & Cluster [20] except from the temporal length of each sample (we choose 100 time-frames instead of 50) and replication of the frames where instead Predict & Cluster [20] uses zero padding for the actions having less than their fixed temporal length.




Figure 1: The **learning curves** of our AE model. We provide train/test accuracy values – *left pane* – and MSE loss – *right pane* – of our proposed model trained on NTU-60 in cross-subject protocol. We observe that our model achieves a stable performance at testing time across training epochs: we claim it to be a favorable characteristic, given the plateau in performance across training epochs.

## 1.2 Model Selection and Hyperparameters

Our model consists of a concatenation of three encoder blocks and three decoder blocks with ReLU activation layers (as depicted in the main paper Section 3.1). Each block is fully-residual, concatenating  $1 \times 1$ ,  $1 \times 3$ , and  $1 \times 1$  padded convolutional layers with stride 1. The decoder blocks use transpose-convolutional layers with the application of batch normalization layers. It is trained for 100 epochs using Adam optimizer with a learning rate of  $10^{-3}$  when the batch size is 128. The hidden representation layer of our model is a fully-connected layer with the size of 2048. We use the features extracted from that layer, which are later given to the classifiers (*i.e.*, 1-NN protocol [20] or Linear Evaluation Protocol [26] (see the main paper Section 3.4 for the definitions). In Figure 1, the learning curves of our model after applying z-normalization are given. As seen in this figure, our model achieves a stable performance at testing time across training epochs. This is an affirmative characteristic, also showing that we are able to learn representations without over-training.

## 1.3 Implementation of Self-supervised Viewpoints Invariance (SSVI)

For the SSVI experiments (see main paper Section 4.2), we rotated the data along the z-axis. For the fully connected layer of GRL, we apply a sigmoid activation function multiplied by  $2\pi$  to match the Euler rotation angle. The GRL loss is an  $L1$  loss calculated between the original Euler angle of rotations and the predicted Euler angle. Additionally, we use a penalty term included in the GRL loss and a penalty term for the GRL layer (*i.e.*, the alpha value depicted in [4]): both are set to  $10^{-3}$ .

## 2 The effect of initialization of Graph Laplacian Weight Matrix

In this section, we want to examine how the initialization of Graph Laplacian weight matrix  $W$  affects our proposed method’s performance: AE-L. As mentioned in the main paper, we want to promote the alignment of skeletal joints, connected through a bone (*e.g.*, ***an edge exists if and only if joints are connected***). The reason behind this is to inject the knowledge of skeletal geometry while learning our action representations. This is referred as *fixed  $W$* , a binary and symmetric  $n \times n$  skeleton adjacency matrix, including the connectivity between

pairs of skeletal joints (as shown in Figure 2 *left*).  $n$  is equal to the number of joints of each skeleton (*e.g.*, 25 joints for NTU-60 [16] and NTU-120 [17]). The  $W_{ij}$  entries of  $\mathbf{W}$  are defined such that  $W_{ij} = 1$  if and only if the joints  $i$  and  $j$  are connected through an edge (in this case a *bone*), 0 otherwise.

A natural alternative to this approach is randomly initializing the weight matrix  $\mathbf{W}$  ( $n \times n$ ). Herein we called this *random W*, and its range is  $[0, 1]$ . We compare the performance of AE-L with *fixed W* (our proposal) against *random W* in Figure 2 rightmost. As seen, *fixed W* achieves better performance than *random W* with a margin of 1.5-2.8% for all settings: cross-subject, cross-view, and cross-setup.

### 3 Confusion matrices

The confusion matrices for testing our AE-L performance within 1-NN protocol [17] for datasets NTU-60 [16] (cross-subject, cross-view) are given in Figure 3. In the same figure, we also report the accuracy score of each action class in the box-plot form.

#### 3.1 Accuracy-per-action class comparison

Our AE-L achieves recognition accuracy above 80% for 8 actions (*sitting down, standing up from sitting position, wearing jacket, taking off jacket, jumping up, falling, walking towards each other, and walking apart from each other*) in NTU-60 cross-subject setting [16].

In NTU-60 cross-view setting [16], our AE-L performs recognition above 90% accuracy for 13 actions (*throwing, sitting down, standing up from sitting position, wearing jacket, taking off jacket, cheering up, kicking something, one foot jumping, jumping up, salute, crossing hands in front, staggering, and falling*) while class accuracy above 80% is observed for 41 actions.

There are 3 actions: *standing up from sitting position, jumping, and falling* for which AE-L recognizes with nearly 100% accuracy in cross-view setting of NTU-60 [16].

#### 3.2 Accuracy improvements of Laplacian regularization on cross-subject protocol

As shown in the main paper, AE-L improves the performance of the AE model, showing that Laplacian regularization supplies some advantages.




Figure 2: **Skeletal Laplacian Regularization.** *Left*: location of the skeletal joints on NTU-60 [16]. *Center*: corresponding adjacency matrix  $\mathbf{W}$  (binary). *Right*: ablation table on overall accuracy of AE-L *w.r.t.* using a fixed Laplacian weight matrix, *i.e.*, skeleton adjacency matrix (our proposal) or randomized one.

For NTU-60 cross-subject action classes: *brushing hair, drop, reading, wear on glasses, take off glasses and using a fan* and for NTU-120 cross-subject action classes; *taking off a shoe, wearing on glasses, making a phone call, putting the palms together, patting on back of other person, applying cream on face and kicking backward*; we obtained at least +5% performance gain by involving Laplacian regularization to our AE.

### 3.3 Accuracy improvements of Laplacian regularization on cross-view and cross-setup protocols

Additionally, our AE-L performs at least +5% better than our AE for NTU-60 cross-view and NTU-120 cross-setup actions.

The NTU60 cross-view actions are: *eating meal, brushing teeth, brushing hair, dropping, clapping, reading, tearing up paper, wearing on glasses, taking off glasses, putting on a hat, taking off a hat, reaching into pocket, hopping, make a phone call, playing with phone, taking a selfie, checking time, rubbing two hands together, wiping face, putting the palms together, sneeze/cough, touching head/chest/back, using a fan, punching other person, patting on back of other person and touching other person's pocket*.

In addition, the NTU-120 cross-setup action classes are: *drinking water, eating meal, putting on a hat, taking off a hat, kicking something, making a phone call, putting the palms together, kicking other person, hushing, thumbing up, making victory sign, sniffing, balling up paper, applying cream on face, taking something out of a bag and crossing arms*.




Figure 3: Confusion matrices and the corresponding accuracy scores for each action class obtained when our AE-L is applied with 1-NN protocol on the NTU-60 [16] dataset.

## 4 Comparisons with state-of-the-art skeleton-based HAR

Performance comparisons between our AE-L and the state-of-the-art unsupervised and supervised skeleton-based HAR methods on NTU-60 dataset [16] are given in Figure 4 (equivalent to Figure 4 in the main paper). The results in Table 1 provide the quantitative values, which are summarised in Figure 4.

Our AE-L outperforms all prior unsupervised skeleton-based approaches on the cross-subject and cross-view settings. Importantly, our learnable representation, although being unsupervised, allows our method to even surpass a few supervised skeleton-based action recognition methods: [10, 6, 11, 13, 15, 24].




Figure 4: Comparisons between our AE-L and SOTA unsupervised and supervised skeleton-based HAR methods on NTU-60 dataset [16].

	Method	Classifier	Architecture	Cross-Subject	Cross-View
Rahmani et al. (2016) [10]	supervised	linear SVM	3D Spatio-temporal interest points	<u>50.1</u>	<u>52.8</u>
Cavazza et al. (2019) [6]	supervised	linear SVM	Kernel-approximating random feat maps	<u>60.9</u>	63.4
Du et al. (2015) [11]	supervised	softmax	Hierarchical RNN	<u>59.1</u>	64.0
Liu et al. (2016) [13]	supervised	softmax	Spatial Temporal LSTM	<u>69.2</u>	<u>77.7</u>
Shahroudy et al. (2016) [15]	supervised	softmax	Part-Aware LSTM	<u>62.9</u>	<u>70.3</u>
Kim et al. (2017) [9]	supervised	softmax	Temporal CNN	74.3	83.1
Zhang et al. (2017) [14]	supervised	softmax	View-Adaptive LSTM	79.2	87.7
Liu et al. (2017) [12]	supervised	softmax	Multi-stream CNN	80.0	87.2
Liu et al. (2017) [8]	supervised	softmax	CNN	83.2	89.3
Yan et al. (2018) [17]	supervised	softmax	Spatio-Temporal GCN	81.5	88.3
Wen et al. (2019) [24]	supervised	softmax	Motif GCN + Variable Temporal Dense Block	84.2	90.2
Li et al. (2019) [7]	supervised	softmax	Actional-structural GCN	86.8	94.2
Shi et al. (2019) [18]	supervised	softmax	2-stream Adaptive GCN	88.5	95.1
Si et al. (2019) [19]	supervised	softmax	Attention GCN+LSTM	89.2	95.0
Shi et al. (2019) [20]	supervised	softmax	Directed Graph Neural Networks	89.9	96.1
Cheng et al. (2020) [9]	supervised	softmax	Shift GCN	<u>90.7</u>	<u>96.5</u>
Holden et al. (2015) [8]	unsupervised	linear classifier	Denoising AE	<u>61.2</u>	<u>70.2</u>
Zheng et al. (2018) [14]	unsupervised	linear classifier	Adversarial GRU-AE	<u>39.1</u>	<u>48.1</u>
Kundu et al. (2018) [9]	unsupervised	linear classifier	Variational-AE + poseRNN	<u>56.4</u>	<u>63.8</u>
Kundu et al. (2018) [9]	unsupervised	linear classifier	Encoder-GAN + poseRNN	<u>68.6</u>	<u>77.8</u>
Xu et al. (2020) [21]	unsupervised	linear classifier	Contrastive-AE	<u>53.9</u>	<u>63.5</u>
Rao et al. (2020) [22]	unsupervised	linear classifier	Contrastive-AE	<u>58.5</u>	<u>64.6</u>
Li et al. (2021) [9]	unsupervised	linear classifier	Contrastive-GCN	<u>68.3</u>	<u>76.4</u>
<b>Our AE-L</b>	unsupervised	linear classifier	Regularized convolutional, residual AE	<b>69.9</b>	<b>85.4</b>

Table 1: Performance comparisons between our AE-L and the state-of-the-art supervised and unsupervised skeleton-based HAR methods on NTU-60 dataset [16] in terms of accuracy (%). The results that our AE-L surpasses are underlined. The best results for the supervised and unsupervised methods individually are shown in black.

## 5 Visualization of the reconstructed skeletons

Figures 5 and 6 present the visualizations of the reconstructed skeletons obtained by applying our models (AE and AE-L). *Blue* skeletons represent the input data (of action "Drink Water" for Figure 5 and "Standing Up" for Figure 6), *red* and *green* skeletons are reconstructed by AE and AE-L, respectively. In these examples, while the effectiveness of our models is the same, in other words, AE and AE-L both classify the actions correctly, the AE-L makes the reconstructed skeletons smoother compared to AE.




Figure 5: Action class "Drink Water" in NTU-60 [16] cross-view dataset. *Blue*: original data, *Red*: AE reconstruction, *Green*: AE-L reconstruction. Columns correspond to different time-frames. Both AE and AE-L correctly classify this action sample.




Figure 6: Action class "Standing Up" in NTU-60 [16] cross-view dataset. *Blue*: original data, *Red*: AE reconstruction, *Green*: AE-L reconstruction. Columns correspond to different time-frames. Both AE and AE-L correctly classify this action sample.

## References

- [1] Jacopo Cavazza, Pietro Morerio, and Vittorio Murino. Scalable and compact 3D action recognition with approximated rbf kernel machines. *Pattern Recognition*, 93:25–35, 2019.
- [2] Chao Li, Qiaoyong Zhong, Di Xie, and Shiliang Pu. Skeleton-based action recognition with convolutional neural networks. In *2017 IEEE International Conference on Multimedia Expo Workshops (ICMEW)*, pages 597–600, 2017. doi: 10.1109/ICMEW.2017.8026285.
- [3] Ke Cheng, Yifan Zhang, Xiangyu He, Weihang Chen, Jian Cheng, and Hanqing Lu. Skeleton-based action recognition with shift graph convolutional network. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 183–192, 2020.
- [4] Yaroslav Ganin and Victor Lempitsky. Unsupervised domain adaptation by backpropagation. In *The International Conference on Machine Learning (ICML)*, 2015.
- [5] Daniel Holden, Jun Saito, Taku Komura, and Thomas Joyce. Learning motion manifolds with convolutional autoencoders. In *SIGGRAPH Asia 2015 Technical Briefs*, 2015.
- [6] T. S. Kim and A. Reiter. Interpretable 3d human action analysis with temporal convolutional networks. In *2017 IEEE Conference on Computer Vision and Pattern Recognition Workshops (CVPRW)*, pages 1623–1631, 2017. doi: 10.1109/CVPRW.2017.207.
- [7] Jogendra Nath Kundu, Maharshi Gor, Phani Krishna Uppala, and R Venkatesh Babu. Unsupervised feature learning of human actions as trajectories in pose embedding manifold. In *IEEE Winter Conference on Applications of Computer Vision (WACV)*, 2018.
- [8] M. Li, S. Chen, X. Chen, Y. Zhang, Y. Wang, and Q. Tian. Actional-structural graph convolutional networks for skeleton-based action recognition. In *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3590–3598, 2019. doi: 10.1109/CVPR.2019.00371.
- [9] Li Linguo, Wang Minsi, Ni Bingbing, Wang Hang, Yang Jiancheng, and Zhang Wenjun. 3d human action representation learning via cross-view consistency pursuit. In *CVPR*, 2021.
- [10] Jun Liu, Amir Shahroudy, Dong Xu, and Gang Wang. Spatio-temporal lstm with trust gates for 3d human action recognition. *arXiv preprint arXiv:1607.07043*, 2016.
- [11] Jun Liu, Amir Shahroudy, Mauricio Perez, Gang Wang, Ling-Yu Duan, and Alex C. Kot. Ntu rgb+d 120: A large-scale benchmark for 3d human activity understanding. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2019. doi: 10.1109/TPAMI.2019.2916873.
- [12] Mengyuan Liu, Hong Liu, and Chen Chen. Enhanced skeleton visualization for view invariant human action recognition. *Pattern Recogn.*, 68:346–362, August 2017. doi: 10.1016/j.patcog.2017.02.030.

- [13] H. Rahmani, A. Mahmood, D. Huynh, and A. Mian. Histogram of oriented principal components for cross-view action recognition. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 38(12):2430–2443, 2016. doi: 10.1109/TPAMI.2016.2533389.
- [14] Haocong Rao, Shihao Xu, Xiping Hu, Jun Cheng, and Bin Hu. Augmented skeleton based contrastive action learning with momentum lstm for unsupervised action recognition, 2020.
- [15] A. Shahroudy, J. Liu, T. Ng, and G. Wang. Ntu rgb+d: A large scale dataset for 3d human activity analysis. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 1010–1019, 2016. doi: 10.1109/CVPR.2016.115.
- [16] Amir Shahroudy, Jun Liu, Tian-Tsong Ng, and Gang Wang. Ntu rgb+d: A large scale dataset for 3d human activity analysis. In *IEEE Conference on Computer Vision and Pattern Recognition*, June 2016.
- [17] Lei Shi, Yifan Zhang, Jian Cheng, and Hanqing Lu. Skeleton-based action recognition with directed graph neural networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2019.
- [18] Lei Shi, Yifan Zhang, Jian Cheng, and Hanqing Lu. Two-stream adaptive graph convolutional networks for skeleton-based action recognition. In *CVPR*, 2019.
- [19] Chenyang Si, Wentao Chen, Wei Wang, Liang Wang, and Tieniu Tan. An attention enhanced graph convolutional lstm network for skeleton-based action recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2019.
- [20] K. Su, X. Liu, and E. Shlizerman. Predict & cluster: Unsupervised skeleton based action recognition. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 9628–9637, 2020. doi: 10.1109/CVPR42600.2020.00965.
- [21] Yu-Hui Wen, Lin Gao, Hongbo Fu, Fang-Lue Zhang, and Shihong Xia. Graph cnns with motif and variable temporal block for skeleton-based action recognition. *Proceedings of the AAAI Conference on Artificial Intelligence*, 33(01):8989–8996, Jul. 2019. doi: 10.1609/aaai.v33i01.33018989. URL <https://ojs.aaai.org/index.php/AAAI/article/view/4929>.
- [22] Shihao Xu, Haocong Rao, Xiping Hu, and Bin Hu. Prototypical contrast and reverse prediction: Unsupervised skeleton based action recognition. In *arXiv preprint 2011.07236*, 2020.
- [23] Sijie Yan, Yuanjun Xiong, and Dahua Lin. Spatial temporal graph convolutional networks for skeleton-based action recognition. *AAAI*, pages 7444–7452, 2018.
- [24] Yong Du, W. Wang, and L. Wang. Hierarchical recurrent neural network for skeleton based action recognition. In *2015 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 1110–1118, 2015. doi: 10.1109/CVPR.2015.7298714.

- 
- [25] Pengfei Zhang, Cuiling Lan, Junliang Xing, Wenjun Zeng, Jianru Xue, and Nanning Zheng. View adaptive recurrent neural networks for high performance human action recognition from skeleton data. In *Proceedings of the IEEE International Conference on Computer Vision (ICCV)*, Oct 2017.
- [26] Nenggan Zheng, Jun Wen, Risheng Liu, Liangqu Long, Jianhua Dai, and Zhefeng Gong. Unsupervised representation learning with long-term dynamics for skeleton based action recognition. In *Proceedings of the AAAI Conference on Artificial Intelligence (AAAI)*, 2018.